GALAXY - BD 1000 GX

GALAXY “GX”



For illustrative purposes only

ENGINE

Engine brand	BAUDOUIN	
Engine model	12M26G1100/5	
Cylinders	12	
Speed	1500	r.p.m.
Cubic capacity	31.80	l
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	0-18	
BMEP	2448	kPa
Cooling	Water	
Flywheel P.R.P. Power	859.0	kW
Flywheel Stand-by Power	943.0	kW
Fuel Cons. at 100% (L.T.P.)	227.4	l/h
Fuel Cons. at 100% (P.R.P)	205.2	l/h
Fuel Cons. at 75% (P.R.P.)	154.0	l/h
Fuel Cons. at 50% (P.R.P.)	105.7	l/h
Fuel Cons. at 25% (P.R.P.)	57.8	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	114.0	l
Engine Antifreeze capacity	83.0	l
Radiator type	Temperate	
Heat from radiator	1299.0	kW
Heat from exhaust	0.0	kW
Heat from radiation	0.0	kW
Exhaust temperature	550	°C
Cooling air flow	840.00	m³/min
Combustion air flow	68.90	m³/min
Exhaust gas flow	253.00	m³/min
TA Luft	Not available	
TA Luft/2	Not available	
EPA	Not available	
Stage	Not available	

MAIN DATA

Continuous power (PRP)	1000.0	(kVA)
Continuous power (PRP)	800.0	(kW)
Stand-by power (LTP)	1100.0	(kVA)
Stand-by power (LTP)	880.0	(kW)
Voltage • Frequency • Power Factor	**400V •50Hz • 0.8 cosφ**	

DIMENSIONS AND WEIGHT

Width	1940	mm
Length	5800	mm
Height	2550	mm
Weight	8800	kg

ALTERNATOR

Alternator brand	STAMFORD	
Alternator model	S6L1D-E	
P.R.P. Power	1050.0	kVA
L.T.P. Power	1125.0	kVA
Connection	Star	
Phases	3P+N	
Winding	6 terminals winding 312	
Terminal Number	6	nr.
IP Protection	23	
Electronic regulator	MX321	
Precision	1.0	± %

BASEFRAME

Model	GV300	
Standard tank	400	l
Optional tank	0	l
Oversized tank*	0	l

CANOPY & SILENCER

Canopy model	GV300	
Silencer model	MSR/A 250	
Silencer outlet diameter	273.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.
P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.
L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1.The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.