GALAXY - V 250 GX

GALAXY “GX”



For illustrative purposes only

MAIN DATA

Continuous power (PRP)	250.0	(kVA)
Continuous power (PRP)	200.0	(kW)
Stand-by power (LTP)	275.0	(kVA)
Stand-by power (LTP)	220.0	(kW)
Voltage • Frequency • Power Factor	**400V •50Hz • 0.8 cosφ**	

ENGINE

Engine brand	VOLVO-PENTA	
Engine model	TAD840GE	
Cylinders	6	
Speed	1500	r.p.m.
Cubic capacity	7.70	l
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	2-11«	
BMEP	2400	kPa
Cooling	Water	
Flywheel P.R.P. Power	220.0	kW
Flywheel Stand-by Power	242.0	kW
Fuel Cons. at 100% (L.T.P.)	60.2	l/h
Fuel Cons. at 100% (P.R.P)	54.0	l/h
Fuel Cons. at 75% (P.R.P.)	40.7	l/h
Fuel Cons. at 50% (P.R.P.)	27.3	l/h
Fuel Cons. at 25% (P.R.P.)	15.3	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	27.0	l
Engine Antifreeze capacity	51.0	l
Radiator type	Tropical	
Heat from radiator	162.0	kW
Heat from exhaust	160.0	kW
Heat from radiation	0.0	kW
Exhaust temperature	536	°C
Cooling air flow	324.00	m³/min
Combustion air flow	15.00	m³/min
Exhaust gas flow	0.00	m³/min
TA Luft	Not available	
TA Luft/2	Not available	
EPA	Not available	
Stage	Stage 2	

DIMENSIONS AND WEIGHT

Width	1350	mm
Length	3770	mm
Height	2270	mm
Weight	3160	kg

ALTERNATOR

Alternator brand	STAMFORD	
Alternator model	UCDI274K	
P.R.P. Power	250.0	kVA
L.T.P. Power	275.0	kVA
Connection	Series star	
Phases	3P+N	
Winding	12 terminals Winding 311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS440	
Precision	1.0	± %

BASEFRAME

Model	GV121	
Standard tank	500	l
Optional tank	0	l
Oversized tank*	0	l

CANOPY & SILENCER

Canopy model	GV121	
Silencer model	MSR/a 100	
Silencer outlet diameter	114.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.
P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.
L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1.The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.